




RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
77.47 CX	±0.19	3	0.5	90%	50.80	+0/-0.025	H-K9L	517642	9.00	±0.10
Plano	-	3	0.5	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED  $\pm 0.10$
3. MATERIAL: OPTICAL GLASS H-K9L
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 150.00±1%
7. SURFACE QUALITY : 40-20 SCRATCH-DIG
8. CHAMFER EDGES: 0.5×45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 1.0' MINUTES MAX
10. COATING: S1 & S2: Ravg<0.35% @ 420-680nm @ 0° AOI

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DIMENSIONS ARE IN mm		DRAWN	Sally Song	
TOLERANCES:		CHECK		
FRACTIONAL $\pm$		ENG APPR.		
ANGULAR: $\pm 3$ ARC MIN		MFG APPR.		
TWO PLACE DECIMAL: $\pm 0.10$		QA	Ann Chen	12.18.24
THREE PLACE DECIMAL: $\pm 0.05$		COMMENTS		
INTERPRET GEOMETRIC TOLERANCING PER:				TITLE:
MATERIAL H-K9L				DIAMETER 50.80MM, EFL 150.00MM, H-K9L, VIS O COATED, PLANO-CONVEX LENS
FINISH		SIZE	DWG.NO.	REV
		<b>A</b>	L-PX003015050Z	<b>0</b>
DO NOT SCALE DRAWING	PROJECT NO.	SCALE:	WEIGHT:	SHEET 1 OF 1