



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
77.47 CX	±0.19	3	0.5	90%	40.00	+0/-0.025	H-K9L	517642	5.00	±0.10
Plano	-	3	0.5	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: OPTICAL GLASS H-K9L
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 150.00±1%
7. SURFACE QUALITY : 40-20 SCRATCH-DIG
8. CHAMFER EDGES: 0.5×45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 1.0' MINUTES MAX
10. COATING: UNCOATED

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	
DIMENSIONS ARE IN mm		Sally Song	9.14.24	
TOLERANCES:		DRAWN		TITLE: DIAMETER 40.00MM, EFL 150.00MM, H-K9L PLANO CONVEX LENSES
FRACTIONAL ±		CHECK		
ANGULAR: ±3 ARC MIN		ENG APPR.		
TWO PLACE DECIMAL: ±0.10		MFG APPR.		
THREE PLACE DECIMAL: ±0.05		QA		SIZE A
INTERPRET GEOMETRIC TOLERANCING PER:		COMMENTS		
MATERIAL H-K9L				REV 0
FINISH				
DO NOT SCALE DRAWING		PROJECT NO.		SCALE: WEIGHT: SHEET 1 OF 1