



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
76.285 CX	±0.15	3	1	90%	25.00	-0.05/-0.10	N-BK7	517-642	6.00	±0.10
54.552	±0.11	3	1	90%	25.00	+0/-0.05	N-SF5	673-323	2.40	±0.10
162.446 CX	±0.32	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: $0.5 \times 45^\circ$ MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 125MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: UNCOATED
12. CEMENT USING NORLAND NOA61 OR EQUIVALENT

								
UNLESS OTHERWISE SPECIFIED:			NAME	DATE	TITLE: DIAMETER 25MM, EFL 125MM, ACHROMAT LENS			
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song	12.10.24				
		CHECK						
		ENG APPR.						
		MFG APPR.			SIZE DWG.NO. REV A L-AC0010125025 0			
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24				
MATERIAL		COMMENTS						
FINISH								
DO NOT SCALE DRAWING		PROJECT NO.			SCALE: 1:1		WEIGHT:	SHEET 1 OF 1