



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
435.54 CX	±0.25%	3	1	90%	50.00	-0.1/-0.2	N-BK7	517-642	7.30	±0.10
305.24	±0.25%	3	1	90%	50.00	+0/-0.1	H-F3	617-367	2.00	±0.10
1297.04 CX	±0.25%	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: 0.5×45° MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 750MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: UNCOATED
12. CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:		NAME	DATE		
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL $\pm$ ANGULAR: ± 3 ARC MIN TWO PLACE DECIMAL: ± 0.10 THREE PLACE DECIMAL: ± 0.05	DRAWN	Sally Song	12.16.24		
	CHECK				
	ENG APPR.				
	MFG APPR.				
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen	12.18.24	TITLE: DIAMETER 50MM, EFL 750MM, ACHROMAT LENS	
MATERIAL	COMMENTS			SIZE	DWG.NO.
FINISH				A	L-AC0010750050
DO NOT SCALE DRAWING	PROJECT NO.			SCALE: 1:1	WEIGHT:
				SHEET 1 OF 1	

REV
0