



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
175.95 CX	±0.35	3	2	90%	50.80	-0.05/-0.10	N-BK7	517-642	6.00	±0.10
123.04	±0.25	3	2	90%	50.80	+0.05/-0.10	H-F3	617-367	4.00	±0.10
-506.07 CX	±1.01	3	2	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: $0.5 \times 45^\circ$ MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 300MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: UNCOATED
12. CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:		NAME		DATE							
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song		12.10.24		TITLE: DIAMETER 50.8MM, EFL 300MM, ACHROMAT LENS				
		CHECK									
		ENG APPR.									
		MFG APPR.									
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen		12.18.24		SIZE DWG.NO. A L-AC001030050Z REV 0				
MATERIAL		COMMENTS									
FINISH											
DO NOT SCALE DRAWING		PROJECT NO.				SCALE: 1:1		WEIGHT:		SHEET 1 OF 1	