



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
140.54 CX	±0.25%	5	2	90%	75.00	-0.1/-0.2	N-BK7	517-642	13.70	±0.10
112.81	±0.25%	5	2	90%	75.00	+0.05/-0.1	N-SF2	648-338	5.00	±0.10
430.15 CX	±0.25%	5	2	90%						



SECTION A-A

Notes:

- ALL DIMENSIONS IN MM
- TOLERANCE UNLESS SPECIFIED ± 0.10
- MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
- MANUFACTURE PER MIL-PRF-13830
- POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
- SURFACE QUALITY : 60-40 SCRATCH-DIG
- CHAMFER EDGES: 0.5×45° MAX UNLESS SPECIFIED
- CENTRATION TOLERANCE: 3.0' MINUTES MAX
- EFL: 250MM $\pm 2\%$
- DESIGN WAVELENGTH: 587.6NM
- COATING: UNCOATED
- CEMENT USING NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:			NAME	DATE		
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song	12.10.24	TITLE: DIAMETER75.00MM, EFL 250MM, ACHROMAT LENS	
		CHECK				
		ENG APPR.				
		MFG APPR.				
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24	SIZE DWG.NO. REV A L-AC1010250075 0	
MATERIAL		COMMENTS				
FINISH						
DO NOT SCALE DRAWING		PROJECT NO.			SCALE: 1:1 WEIGHT: SHEET 1 OF 1	