



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
64.43 CX	±0.16	3	1	90%	40.00	+0/-0.10	H-K9L	517642	8.30	±0.10
64.43 CX	±0.16	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: GRADE B, FA PER MIL-G-174, CDGM OR EQUIVALENT, ROHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 63.5mm $\pm 2\%$
7. SURFACE QUALITY : 60-40 SCRATCH-DIG
8. CHAMFER EDGES: 0.5 $\times$ 45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE:3.0' MINUTES MAX
10. COATING:NONE

UNLESS OTHERWISE SPECIFIED:		NAME		DATE						
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05	DRAWN	Sally Song		03.26.25		TITLE: DIAMETER 40MM, EFL 63.5MM, H-K9L BICONVEX LENS				
	CHECK									
	ENG APPR.									
	MFG APPR.									
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen		01.18.25		SIZE DWG.NO. REV A L-DX0010064040 0				
MATERIAL H-K9L	COMMENTS									
FINISH										
DO NOT SCALE DRAWING	PROJECT NO.				SCALE:		WEIGHT:		SHEET 1 OF 1	