



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
128.16 CX	±0.32	3	1	90%	25.40	+0/-0.10	H-K9L	517642	4.25	±0.10
128.16 CX	±0.32	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: GRADE B, FA PER MIL-G-174, CDGM OR EQUIVALENT, ROHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): 125mm $\pm 2\%$
7. SURFACE QUALITY : 60-40 SCRATCH-DIG
8. CHAMFER EDGES: 0.5 $\times$ 45°MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 3.0' MINUTES MAX
10. COATING: S1 & S2: Ravg<0.5% @1050-1700nm @ 0°AOI

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	 OPTICAL MANUFACTURER FROM CHINA				
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05	DRAWN	Sally Song	03.26.25	TITLE: DIAMETER 25.4MM, EFL 125MM, H-K9L BICONVEX LENS				
	CHECK							
	ENG APPR.							
	MFG APPR.							
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen	01.18.25	SIZE DWG.NO. REV A L-DX006012525Z 0				
MATERIAL H-K9L	COMMENTS							
FINISH								
DO NOT SCALE DRAWING	PROJECT NO.			SCALE:		WEIGHT:	SHEET 1 OF 1	