



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
-155.47 CC	±0.31	3	1	90%	75.00	+0/-0.10	H-K9L	517642	2.50	±0.10
155.47 CC	±0.31	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL: H-K9L, GRADE B, FA PER MIL-G-174, CDGM OR EQUIVALENT, ROHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. FOCAL LENGTH(EFL): $-150 \pm 2\%$
7. SURFACE QUALITY : 60-40 SCRATCH-DIG
8. CHAMFER EDGES: $0.5 \times 45^\circ$ MAX UNLESS SPECIFIED
9. CENTRATION TOLERANCE: 3.0' MINUTES MAX
10. COATING: UNCOATED

UNLESS OTHERWISE SPECIFIED:		NAME	DATE		
DIMENSIONS ARE IN mm		DRAWN			
TOLERANCES:		CHECK		TITLE: DIAMETER 75.00MM, EFL -150MM, H-K9L BICONCAVE LENS	
FRACTIONAL $\pm$		ENG APPR.			
ANGULAR: ± 3 ARC MIN		MFG APPR.			
TWO PLACE DECIMAL: ± 0.10		QA	Ann Chen	01.04.25	SIZE A
THREE PLACE DECIMAL: ± 0.05		COMMENTS			
INTERPRET GEOMETRIC TOLERANCING PER:					
MATERIAL H-K9L					DWG.NO. L-DC0010150075
FINISH					
DO NOT SCALE DRAWING		PROJECT NO.		SCALE:	WEIGHT:
				SHEET 1 OF 1	