



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
88.24 CX	±0.18	3	1	90%	40.00	-0.05/-0.10	N-BK7	517-642	7.90	±0.10
-66.23	±0.13	3	1	90%	40.00	+0/-0.05	N-SF2	648-339	3.00	±0.10
-228.36 CX	±0.46	3	1	90%						



SECTION A-A

Notes:

- ALL DIMENSIONS IN MM
- TOLERANCE UNLESS SPECIFIED ± 0.10
- MATERIAL GRADE B, FA PER MIL-G-174,SCHOTT OR EQUIVALENT,ROHS COMPLIANT
- MANUFACTURE PER MIL-PRF-13830
- POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
- SURFACE QUALITY : 60-40 SCRATCH-DIG
- CHAMFER EDGES: 0.5×45°MAX UNLESS SPECIFIED
- CENTRATION TOLERANCE: 3.0' MINUTES MAX
- EFL:150MM±2%
- DESIGN WAVELENGTH:587.6NM
- COATING: S1 & S3: Ravg<0.35% @ 420-680nm @ 0° AOI
- CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:			NAME	DATE	 OPTICAL MANUFACTURER FROM CHINA TITLE: DIAMETER 40MM, EFL 150MM, VIS 0 COATED, ACHROMAT LENS		
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song	12.14.24			
		CHECK					
		ENG APPR.					
		MFG APPR.					
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24	SIZE DWG.NO. REV A L-AC0030150040 0		
MATERIAL	COMMENTS						
FINISH							
DO NOT SCALE DRAWING	PROJECT NO.			SCALE: 1:1		WEIGHT:	SHEET 1 OF 1