



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
175.95 CX	±0.35	3	2	90%	50.80	-0.05/-0.10	N-BK7	517-642	6.00	±0.10
123.04	±0.25	3	2	90%	50.80	+0.05/-0.10	H-F3	617-367	4.00	±0.10
-506.07 CX	±1.01	3	2	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: 0.5x45° MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 300MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: S1 & S3: Ravg < 0.35% @ 420-680nm @ 0° AOI
12. CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:						
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL $\pm$ ANGULAR: ± 3 ARC MIN TWO PLACE DECIMAL: ± 0.10 THREE PLACE DECIMAL: ± 0.05	DRAWN	Sally Song	12.10.24			
	CHECK					
	ENG APPR.					
	MFG APPR.					
	QA	Ann Chen	12.18.24			
INTERPRET GEOMETRIC TOLERANCING PER:	COMMENTS			TITLE: DIAMETER 50.8MM, EFL 300MM, VIS 0 COATED, ACHROMAT LENS		
MATERIAL						
FINISH						
DO NOT SCALE DRAWING	PROJECT NO.			SIZE A	DWG.NO. L-AC003030050Z	REV 0
				SCALE: 1:1	WEIGHT:	SHEET 1 OF 1