



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
243.44 CX	±0.5%		2	95%	72.00	-0.02/-0.1	N-BK7	517-642	11.00	±0.10
181.76	±0.5%		2	95%	72.00	+0.05/-0.02	N-SF5	673-322	5.50	±0.10
539.95 CX	±0.5%		2	95%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: $0.5 \times 45^\circ$ MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 400MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: S1 & S3: $R_{avg} < 0.35\%$ @ 420-680nm @ 0° AOI
12. CEMENT USING NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:							
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL $\pm$ ANGULAR: ± 3 ARC MIN TWO PLACE DECIMAL: ± 0.10 THREE PLACE DECIMAL: ± 0.05	DRAWN	Sally Song	12.16.24	 TITLE: DIAMETER 72MM, EFL 400MM, VIS 0 COATED, ACHROMAT LENS			
	CHECK						
	ENG APPR.						
	MFG APPR.						
INTERPRET GEOMETRIC TOLERANCING PER:	QA	Ann Chen	12.18.24				
MATERIAL	COMMENTS			SIZE	DWG.NO.	REV	
FINISH				A	L-AC0030400072	0	
DO NOT SCALE DRAWING	PROJECT NO.			SCALE: 1:1		WEIGHT:	SHEET 1 OF 1