



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
90.01 CX	±0.18	3	1	90%	50.00	-0.05/-0.10	N-BK7	517-642	11.50	±0.10
66.21	±0.13	3	1	90%	50.00	+0/-0.05	N-SF2	648-338	4.00	±0.10
219.79 CX	±0.44	3	1	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: $0.5 \times 45^\circ$ MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: $150\text{MM} \pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: S1 & S3: SINGLE LAYER MGF2@550NM PER MIL-C-675C, MODERATE ABRASION
12. CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

UNLESS OTHERWISE SPECIFIED:			NAME	DATE	 OPTICAL MANUFACTURER FROM CHINA			
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN			TITLE: DIAMETER 50MM, EFL 150MM, MgF2 COATED, ACHROMAT LENS			
		CHECK						
		ENG APPR.						
		MFG APPR.						
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24	SIZE DWG.NO. REV A L-AC0020150050 0			
MATERIAL		COMMENTS						
FINISH								
DO NOT SCALE DRAWING		PROJECT NO.			SCALE: 1:1		WEIGHT:	SHEET 1 OF 1