



RADIUS	R TOL	POWER	IRRG	CA	DIA	DIA TOL	MATERIAL	INDEX	CT	CT TOL
210.88 CX	±0.50	5	2	90%	76.20	-0.1/-0.2	N-BK7	517-642	10.00	±0.10
186.63	±0.45	5	2	90%	76.20	+0.05/-0.1	N-SF2	648-338	5.00	±0.10
857.37 CX	±2.00	3	2	90%						



SECTION A-A

Notes:

1. ALL DIMENSIONS IN MM
2. TOLERANCE UNLESS SPECIFIED ± 0.10
3. MATERIAL GRADE B, FA PER MIL-G-174, SCHOTT OR EQUIVALENT, RoHS COMPLIANT
4. MANUFACTURE PER MIL-PRF-13830
5. POLISH TO TESTPLATE WITHIN POWER AND IRREGULARITY INDICATED (FRINGES)
6. SURFACE QUALITY : 60-40 SCRATCH-DIG
7. CHAMFER EDGES: 0.5×45° MAX UNLESS SPECIFIED
8. CENTRATION TOLERANCE: 3.0' MINUTES MAX
9. EFL: 400MM $\pm 2\%$
10. DESIGN WAVELENGTH: 587.6NM
11. COATING: S1 & S3: SINGLE LAYER MGF2@550NM PER MIL-C-675C, MODERATE ABRASION
12. CEMENT USUNG NORLAND NOA61 OR EQUIVALENT

								
UNLESS OTHERWISE SPECIFIED:			NAME	DATE	TITLE: DIAMETER 76.2MM, EFL 400MM, MgF2 COATED, ACHROMAT LENS			
DIMENSIONS ARE IN mm TOLERANCES: FRACTIONAL ± ANGULAR: ±3 ARC MIN TWO PLACE DECIMAL: ±0.10 THREE PLACE DECIMAL: ±0.05		DRAWN	Sally Song	12.10.24				
		CHECK						
		ENG APPR.						
		MFG APPR.						
INTERPRET GEOMETRIC TOLERANCING PER:		QA	Ann Chen	12.18.24	SIZE DWG.NO. A L-AC002040076Z			
MATERIAL		COMMENTS						
FINISH								
DO NOT SCALE DRAWING		PROJECT NO.			SCALE: 1:1		WEIGHT:	SHEET 1 OF 1